

LENA SURFACE

The Unlimited Possibilities

PRODUCT DESCRIPTION

MOUNTING	SURFACE
LIGHT SOURCE	LED
LIGHT DISTRIBUTION	DIRECT
MATERIALS	ALUMINIUM
LUMINAIRE TYPE	SYSTEM

Minimalist, classic and playful, the Lena is a customisable curved linear system based on straight lines and curved sections.

The wide selection of curved lighting profiles gives the designer freedom to design completely unique architectural lighting systems. Mix the straight linear lighting sections with the curved sections and create unique abstract shapes. Combine the curved sections and create an endless wave pendant light.

PRODUCT CODE

LENA SURFACE			
R (°)	Low Output - Direct		
45°	LED	315mm / 1200 lm/m	87-F*1-F1-315X45D-***-***
45°	LED	448mm / 1200 lm/m	87-F*1-F1-448X45D-***-***
45°	LED	595mm / 1200 lm/m	87-F*1-F1-595X45D-***-***
45°	LED	805mm / 1200 lm/m	87-F*1-F1-805X45D-***-***
45°	LED	959mm / 1200 lm/m	87-F*1-F1-959X45D-***-***
45°	LED	1171mm / 1200 lm/m	87-F*1-F1-1171X45D-***-***
45°	LED	1575mm / 1200 lm/m	87-F*1-F1-1575X45D-***-***
60°	LED	316mm / 1200 lm/m	87-F*1-F1-316X60D-***-***
60°	LED	419mm / 1200 lm/m	87-F*1-F1-419X60D-***-***
60°	LED	597mm / 1200 lm/m	87-F*1-F1-597X60D-***-***
60°	LED	1074mm / 1200 lm/m	87-F*1-F1-1074X60D-***-***
60°	LED	1278mm / 1200 lm/m	87-F*1-F1-1278X60D-***-***
60°	LED	1561mm / 1200 lm/m	87-F*1-F1-1561X60D-***-***
60°	LED	2100mm / 1200 lm/m	87-F*1-F1-2100X60D-***-***
90°	LED	474mm / 1200 lm/m	87-F*1-F1-474X90D-***-***
90°	LED	629mm / 1200 lm/m	87-F*1-F1-629X90D-***-***
90°	LED	896mm / 1200 lm/m	87-F*1-F1-896X90D-***-***
90°	LED	1190mm / 1200 lm/m	87-F*1-F1-1190X90D-***-***
90°	LED	1610mm / 1200 lm/m	87-F*1-F1-1610X90D-***-***
90°	LED	1917mm / 1200 lm/m	87-F*1-F1-1917X90D-***-***
90°	LED	2341mm / 1200 lm/m	87-F*1-F1-2341X90D-***-***
120°	LED	632mm / 1200 lm/m	87-F*1-F1-632X120D-***-***
120°	LED	838mm / 1200 lm/m	87-F*1-F1-838X120D-***-***
120°	LED	1194mm / 1200 lm/m	87-F*1-F1-1194X120D-***-***
120°	LED	1587mm / 1200 lm/m	87-F*1-F1-1587X120D-***-***
120°	LED	2147mm / 1200 lm/m	87-F*1-F1-2147X120D-***-***
135°	LED	711mm / 1200 lm/m	87-F*1-F1-711X135D-***-***
135°	LED	943mm / 1200 lm/m	87-F*1-F1-943X135D-***-***
135°	LED	1343mm / 1200 lm/m	87-F*1-F1-1343X135D-***-***
135°	LED	1785mm / 1200 lm/m	87-F*1-F1-1785X135D-***-***
L (mm)			
580	LED	580mm / 1200 lm/m	87-F*1-F1-580-***-***
860	LED	860mm / 1200 lm/m	87-F*1-F1-860-***-***
1140	LED	1140mm / 1200 lm/m	87-F*1-F1-1140-***-***
1420	LED	1420mm / 1200 lm/m	87-F*1-F1-1420-***-***
1700	LED	1700mm / 1200 lm/m	87-F*1-F1-1700-***-***
1980	LED	1980mm / 1200 lm/m	87-F*1-F1-1980-***-***
2260	LED	2260mm / 1200 lm/m	87-F*1-F1-2260-***-***
*Luminous flux taken at 4000K microprismatic diffuser			

OPTICS			
MICROPRISMATIC	OPAL	PRISMATIC OPAL	87-F*1-F1-***-***-D 87-F*1-F1-***-***-C 87-F*1-F1-***-***-B 87-F*1-F1-***-***-RAL###

OUTPUT			
Low Output	Medium Output	Low Output Medium Output	87-F*1-F1-***-***-D 87-F*1-F1-***-***-C
*Low output 1200lm/m *Medium output 1600lm/m			
CRI			
80	90	80 90	87-F*1-F1-***-***-8 87-F*1-F1-***-***-9
COLOUR TEMPERATURE			
3000K	4000K	3000 K 4000 K	87-F*1-F1-***-***-30-*** 87-F*1-F1-***-***-40-***
CONTROL			
NON DIM	DALI DIM	DALI 2 DIM	CASAMBI
NON DIM	DALI DIM	DALI 2 DIM	CASAMBI DIM
NON DIM DALI DIM DALI 2 DIM CASAMBI NON DIM DALI DIM DALI 2 DIM CASAMBI DIM NON DIM DALI DIM DALI 2 DIM CASAMBI DIM NON DIM DALI DIM DALI 2 DIM CASAMBI DIM			
*EasyAir IoT on request			
EMERGENCY			
NO EMERGENCY	3 HOUR NON-REPORTING EMERGENCY	3 HOUR REPORTING EMERGENCY	3 HOUR SELF-TEST EMERGENCY
NO EMERGENCY	3 HOUR NON-REPORTING EMERGENCY	3 HOUR REPORTING EMERGENCY	3 HOUR SELF-TEST EMERGENCY
No Emergency 3 Hour Non Reporting EM 3 Hour Reporting EM 3 Hour Self-Test EM			
*Only available in sizes above 1266mm			
FINISH			
BLACK	WHITE	SILVER	CUSTOMRAL
BLACK	WHITE	SILVER	CUSTOMRAL
BLACK WHITE GREY CUSTOM RAL			

