

LENA SUSPENDED

The Unlimited Possibilities.

PRODUCT DESCRIPTION

MOUNTING	SUSPENDED
LIGHT SOURCE	LED
LIGHT DISTRIBUTION	DIRECT - INDIRECT
MATERIALS	ALUMINIUM
LUMINAIRE TYPE	SYSTEM

Minimalist, classic and playful, the Lena is a customisable curved linear system based on straight lines and curved sections.

The wide selection of curved lighting profiles gives the designer freedom to design completely unique architectural lighting systems. Mix the straight linear lighting sections with the curved sections and create unique abstract shapes. Combine the curved sections and create an endless wave pendant light.

PRODUCT CODE

LENA SUSPENDED			
R (°)	Low Output - Direct - Indirect		
45°	LED	315mm / 1500 lm/m	87-E*3-F1-315X45D-***-***
45°	LED	448mm / 1500 lm/m	87-E*3-F1-448X45D-***-***
45°	LED	595mm / 1500 lm/m	87-E*3-F1-595X45D-***-***
45°	LED	805mm / 1500 lm/m	87-E*3-F1-805X45D-***-***
45°	LED	959mm / 1500 lm/m	87-E*3-F1-959X45D-***-***
45°	LED	1171mm / 1500 lm/m	87-E*3-F1-1171X45D-***-***
45°	LED	1575mm / 1500 lm/m	87-E*3-F1-1575X45D-***-***
60°	LED	316mm / 1500 lm/m	87-E*3-F1-316X60D-***-***
60°	LED	419mm / 1500 lm/m	87-E*3-F1-419X60D-***-***
60°	LED	597mm / 1500 lm/m	87-E*3-F1-597X60D-***-***
60°	LED	1074mm / 1500 lm/m	87-E*3-F1-1074X60D-***-***
60°	LED	1278mm / 1500 lm/m	87-E*3-F1-1278X60D-***-***
60°	LED	1561mm / 1500 lm/m	87-E*3-F1-1561X60D-***-***
60°	LED	2100mm / 1500 lm/m	87-E*3-F1-2100X60D-***-***
90°	LED	474mm / 1500 lm/m	87-E*3-F1-474X90D-***-***
90°	LED	629mm / 1500 lm/m	87-E*3-F1-629X90D-***-***
90°	LED	896mm / 1500 lm/m	87-E*3-F1-896X90D-***-***
90°	LED	1190mm / 1500 lm/m	87-E*3-F1-1190X90D-***-***
90°	LED	1610mm / 1500 lm/m	87-E*3-F1-1610X90D-***-***
90°	LED	1917mm / 1500 lm/m	87-E*3-F1-1917X90D-***-***
90°	LED	2341mm / 1500 lm/m	87-E*3-F1-2341X90D-***-***
120°	LED	632mm / 1500 lm/m	87-E*3-F1-632X120D-***-***
120°	LED	838mm / 1500 lm/m	87-E*3-F1-838X120D-***-***
120°	LED	1194mm / 1500 lm/m	87-E*3-F1-1194X120D-***-***
120°	LED	1587mm / 1500 lm/m	87-E*3-F1-1587X120D-***-***
120°	LED	2147mm / 1500 lm/m	87-E*3-F1-2147X120D-***-***
135°	LED	711mm / 1500 lm/m	87-E*3-F1-711X135D-***-***
135°	LED	943mm / 1500 lm/m	87-E*3-F1-943X135D-***-***
135°	LED	1343mm / 1500 lm/m	87-E*3-F1-1343X135D-***-***
135°	LED	1785mm / 1500 lm/m	87-E*3-F1-1785X135D-***-***
L (mm)			
580	LED	580mm / 1500 lm/m	87-E*3-F1-580-***-***
860	LED	860mm / 1500 lm/m	87-E*3-F1-860-***-***
1140	LED	1140mm / 1500 lm/m	87-E*3-F1-1140-***-***
1420	LED	1420mm / 1500 lm/m	87-E*3-F1-1420-***-***
1700	LED	1700mm / 1500 lm/m	87-E*3-F1-1700-***-***
1980	LED	1980mm / 1500 lm/m	87-E*3-F1-1980-***-***
2260	LED	2260mm / 1500 lm/m	87-E*3-F1-2260-***-***

*Luminous flux taken at 4000K microprismatic diffuser

OPTICS

MICROPRISMATIC	OPAL	PRISMATIC OPAL	87-E*3-F-***-***-D 87-E*3-F-***-***-C 87-E*3-F-***-***-B 87-E*3-F-***-***-A
----------------	------	----------------	--

OUTPUT

Low Output	Medium Output	Low Output Medium Output	87-E*3-F1-***-***-A 87-E*3-F2-***-***-A
		*Low output 1500lm/m *Medium output 2000lm/m	

CRI

80	90	80	87-E*3-F-***-***-G 87-E*3-F-***-***-G

COLOUR TEMPERATURE

3000K	4000K	3000 K 4000 K	87-E*3-F-***-***-30-*** 87-E*3-F-***-***-40-***

CONTROL

NON DIM	DALI DIM	DALI 2 DIM	CASAMBI	NON DIM DALI DIM DALI 2 DIM CASAMBI DIM	87-E*3-F-***-***-J 87-E*3-F-***-***-J 87-E*3-F-***-***-J 87-E*3-F-***-***-J
				*EasyAir IoT on request	

EMERGENCY

NO EMERGENCY	3 HOUR NON-REPORTING EMERGENCY	3 HOUR REPORTING EMERGENCY	3 HOUR SELF-TEST EMERGENCY	No Emergency 3 Hour Non Reporting EM 3 Hour Reporting EM 3 Hour Self-Test EM	87-E*3-F-***-***-0 87-E*3-F-***-***-3 87-E*3-F-***-***-4 87-E*3-F-***-***-5
				*Only available in sizes above 1266mm	

FINISH

BLACK	WHITE	SILVER	CUSTOMRAL	BLACK WHITE GREY CUSTOM RAL	87-E*3-F-***-***-D 87-E*3-F-***-***-C 87-E*3-F-***-***-B 87-E*3-F-***-***-RAL###

