

TALLA SLIM

The Timeless.

PRODUCT DESCRIPTION

MOUNTING	SUSPENDED
LIGHT SOURCE	LED
LIGHT DISTRIBUTION	DIRECT - DIRECT/INDIRECT
MATERIALS	ALUMINIUM
OPTIC	MICROPRISMATIC / OPAL

The architectural office lighting Talla uses the idea of basic geometrical shapes and timeless appearance to produce a luminaire which delivers simplicity at its best. Variation in sizes, multiple colour choices and the selection of dimming options means the Talla can now add a personality to any space.

The option of an opal diffuser gives a clean and contemporary look, with the evenly distributed light enhancing the details of a building's architecture.

TALLA SLIM SUSPENDED DIRECT


L (mm)		
410x24mm	LED 11W /1540lm	35-E**1-F1-410-8***-***
410x24mm	LED 18W /2550lm	35-E**1-F2-410-8***-***
410x24mm	LED 30W /4060lm	35-E**1-F3-410-8***-***
501x24mm	LED 15W /1870lm	35-E**1-F1-501-8***-***
501x24mm	LED 21W /2560lm	35-E**1-F2-501-8***-***
501x24mm	LED 34W /4080lm	35-E**1-F3-501-8***-***
630x24mm	LED 15W /2090lm	35-E**1-F1-630-8***-***
630x24mm	LED 30W /4100lm	35-E**1-F2-630-8***-***
630x24mm	LED 41W /5630lm	35-E**1-F3-630-8***-***
804x24mm	LED 24W /3510lm	35-E**1-F1-804-8***-***
804x24mm	LED 50W /7000lm	35-E**1-F2-804-8***-***
804x24mm	LED 68W /9570lm	35-E**1-F3-804-8***-***

* Luminous Flux taken with 4000K / Opal Diffuser

TALLA SLIM SUSPENDED DIRECT / INDIRECT

L (mm)		
410x24mm	LED 10W /1450lm	35-E**3-F1-410-8***-***
410x24mm	LED 21W /3000lm	35-E**3-F2-410-8***-***
410x24mm	LED 35W /5040lm	35-E**3-F3-410-8***-***
501x24mm	LED 15W /2030lm	35-E**3-F1-501-8***-***
501x24mm	LED 26W /3530lm	35-E**3-F2-501-8***-***
501x24mm	LED 42W /5550lm	35-E**3-F3-501-8***-***
630x24mm	LED 17W /2550lm	35-E**3-F1-630-8***-***
630x24mm	LED 34W /4990lm	35-E**3-F2-630-8***-***
630x24mm	LED 52W /7420lm	35-E**3-F3-630-8***-***
804x24mm	LED 28W /4070lm	35-E**3-F1-804-8***-***
804x24mm	LED 55W /8030lm	35-E**3-F2-804-8***-***
804x24mm	LED 78W /11070lm	35-E**3-F3-804-8***-***

* Luminous Flux taken with 4000K / Opal Diffuser



OPTICS

MICROPRISMATIC	OPAL	MICROPRISMATIC & OPAL	PRISMATIC 35-E**1-F***-8***-*** OPAL 35-E**1-F***-8***-*** PRISMATIC 35-E**1-F***-8***-*** & OPAL
----------------	------	-----------------------	---

*Prismatic & Opal only on Indirect/Direct fittings

COLOUR TEMPERATURE

3000K	4000K	3000K 35-E***-F***-830-***-*** 4000K 35-E***-F***-840-***-***
-------	-------	--

CONTROL

NON DIM	DALI DIM	NON DIM 35-E***-F***-8***-K-*** DALI DIM 35-E***-F***-8***-J-***
---------	----------	---

*PIR Sensor & other controls available on request

EMERGENCY

NON EMERGENCY	3HR NON-REPORTING EMERGENCY	3HR REPORTING EMERGENCY	3HR SELF-TEST EMERGENCY	NON-EMERGENCY 3 HR NON-REPORTING 3 HR REPORTING 3 HR SELF-TEST	35-E***-F***-8***-Q-*** 35-E***-F***-8***-3-*** 35-E***-F***-8***-4-*** 35-E***-F***-8***-5-***
---------------	-----------------------------	-------------------------	-------------------------	--	--

FINISH

BLACK	WHITE	SILVER	BLACK 35-E***-F***-8***-D-*** WHITE 35-E***-F***-8***-C-*** SILVER 35-E***-F***-8***-B-***
-------	-------	--------	--

SUSPENSION

WIRE	ROD	WIRE ROD 35-E***-F***-8***-*** 35-E***-F***-8***-***
------	-----	---