



# OKA SUSPENDED

Class Leading Linear Office Lighting.

## PRODUCT DESCRIPTION

|                           |                            |
|---------------------------|----------------------------|
| <b>MOUNTING</b>           | SUSPENDED                  |
| <b>LIGHT SOURCE</b>       | LED                        |
| <b>LIGHT DISTRIBUTION</b> | DIRECT - INDIRECT / DIRECT |
| <b>MATERIALS</b>          | ALUMINIUM                  |
| <b>OPTICS</b>             | PRS / OPAL                 |


The OKA has all the attributes for setting a new standard for linear office lighting by making a statement in any modern office space. Designed with attention to detail, it will impress the purists with clean lines, homogenous light and a proportionately designed suspension system.

With its 60mm deep frame and wide body, the OKA defines architectural spaces and workspace, making a visual presence even when switched off. Emitting light both up to the ceiling and down onto the workspace, the diamond prismatic lens distributes glare-free lighting with UGR <16 for a healthy working environment. The choice of 4 different colour temperatures suits any application and the light intensity can be dimmed with DALI.

## PRODUCT CODE


### OKA DIRECT-INDIRECT

|               |     |                  |                    |
|---------------|-----|------------------|--------------------|
| l (mm)        |     | High-Efficiency  |                    |
| 1200          | LED | 51W / 5,820 lm   | 52-E*3-F58-8***.*  |
| 1500          | LED | 64W / 7,230 lm   | 52-E*3-F72-8***.*  |
| 2400          | LED | 102W / 11,639 lm | 52-E*3-F11-8***.*  |
| 3000          | LED | 127W / 14,460 lm | 52-E*3-F14-8***.*  |
| High-Output   |     |                  |                    |
| 1200          | LED | 73W / 7,956 lm   | 52-E*3-F79-8***.*  |
| 1500          | LED | 91W / 9,885 lm   | 52-E*3-F98-8***.*  |
| 2400          | LED | 145W / 15,912 lm | 52-E*3-F15-8***.*  |
| 3000          | LED | 181W / 19,769 lm | 52-E*3-F19-8***.*  |
| Tunable White |     |                  |                    |
| 1200          | LED | 53W / 5,982 lm   | 52-E*3-F59-827**.* |
| 1500          | LED | 66W / 7,432 lm   | 52-E*3-F74-827**.* |
| 2400          | LED | 105W / 11,964 lm | 52-E*3-F12-827**.* |
| 3000          | LED | 130W / 14,864 lm | 52-E*3-F13-827**.* |



### OKA DIRECT

|               |     |                 |                    |
|---------------|-----|-----------------|--------------------|
| l (mm)        |     | High-Efficiency |                    |
| 1200          | LED | 27W / 3,226lm   | 52-E*1-F32-8***.*  |
| 1500          | LED | 33W / 3,984 lm  | 52-E*1-F39-8***.*  |
| 2400          | LED | 53W / 6,451 lm  | 52-E*1-F64-8***.*  |
| 3000          | LED | 65W / 7,968 lm  | 52-E*1-F79-8***.*  |
| High-Output   |     |                 |                    |
| 1200          | LED | 38W / 4,410 lm  | 52-E*1-F44-8***.*  |
| 1500          | LED | 47W / 5,447 lm  | 52-E*1-F54-8***.*  |
| 2400          | LED | 75W / 8,819 lm  | 52-E*1-F88-8***.*  |
| 3000          | LED | 93W / 10,894 lm | 52-E*1-F10-8***.*  |
| Tunable White |     |                 |                    |
| 1200          | LED | 28W / 3,316 lm  | 52-E*1-F33-827**.* |
| 1500          | LED | 34W / 4,096 lm  | 52-E*1-F40-827**.* |
| 2400          | LED | 55W / 6,631 lm  | 52-E*1-F66-827**.* |
| 3000          | LED | 67W / 8,191 lm  | 52-E*1-F81-827**.* |



### OPTICS

|                |      |      |                              |
|----------------|------|------|------------------------------|
| MICROPRISMATIC | OPAL | PRS  | 52-E*F**.*-F**.*-8**.*-***.* |
|                |      | OPAL | 52-E*H**.*-F**.*-8**.*-***.* |

### COLOUR TEMPERATURE

|             |        |       |                         |
|-------------|--------|-------|-------------------------|
| 3000 K      | 4000 K | 3000K | 52-E***-F**.*-830-***.* |
|             |        | 4000K | 52-E***-F**.*-840-***.* |
|             |        | TW    | 52-E***-F**.*-827-***.* |
| TW          |        |       |                         |
| 2700K-5000K |        |       |                         |

\* Luminous Flux taken at 3000K

### CONTROL

|               |                    |             |                           |
|---------------|--------------------|-------------|---------------------------|
| NON DIM       | DALI DIM           | NON DIM     | 52-E***-F**.*-g**.*-I**.* |
|               |                    | DALI DIM    | 52-E***-F**.*-g**.*-J**.* |
|               |                    | T. WHITE    | 52-E***-F**.*-g**.*-H**.* |
|               |                    | B. DALI DIM | 52-E***-F**.*-g**.*-M**.* |
| TUNABLE WHITE | BLUETOOTH DALI DIM |             |                           |

### EMERGENCY

|              |                  |      |                           |
|--------------|------------------|------|---------------------------|
| NO EMERGENCY | 3 HOUR EMERGENCY | 0 HR | 52-E***-F**.*-g**.*-0**.* |
|              |                  | 3 HR | 52-E***-F**.*-g**.*-3**.* |

\*Integral Emergency on all sizes

### FINISH

|       |       |       |                            |
|-------|-------|-------|----------------------------|
| WHITE | BLACK | WHITE | 52-E***-F**.*-g**.*-**.*-C |
|       |       | BLACK | 52-E***-F**.*-g**.*-**.*-D |
|       |       | GREY  | 52-E***-F**.*-g**.*-**.*-B |
| GREY  |       |       |                            |

SCAN PRODUCT



SCAN TO VIEW A PROJECT



LITTLE LONDON, LONDON